



(43) International Publication Date
6 April 2006 (06.04.2006)

- (51) International Patent Classification⁷: B60R 25/02
(21) International Application Number: PCT/JP2005/018242

(22) International Filing Date:
27 September 2005 (27.09.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-287622 30 September 2004 (30.09.2004) JP

(71) Applicants (for all designated States except US):
KABUSHIKI KAISHA TOKAI RIKA DENKI
SEISAKUSHO [JP/JP]; 260, Toyota 3-chome,
 Ohguchi-cho, Niwa-gun, Aichi, 4800195 (JP). **TOY-**
OTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1,
 Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).

(72) Inventors: and

(75) **Inventors/Applicants (for US only):** OTANI, Kazuya [JP/JP]; c/o KABUSHIKI KAISHA TOKAI RIKI DENKI SEISAKUSHO, 260, Toyota 3-chome, Ohguchi-cho, Niwa-gun, Aichi, 4800195 (JP). MAEDA, Toru [JP/JP]; c/o KABUSHIKI KAISHA TOKAI RIKI DENKI SEISAKUSHO, 260, Toyota 3-chome, Ohguchi-cho, Niwa-gun, Aichi, 4800195 (JP). NAGAE, Toshitiro

[JP/JP]; c/o KABUSHIKI KAISHA TOKAI RIKAI DENKI
SEISAKUSHO, 260, Toyota 3-chome, Ohguchi-cho,
Niwa-gun, Aichi, 4800195 (JP). **KAKEGAWA, Tomoo**
[JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA,
1, Toyota-cho, Toyota-shi, Aichi, 4718571 (JP).


(74) Agent: ONDA, Hironori; 12-1, Ohmiya-cho 2-chome, Gifu-shi, Gifu-ken 500-8731 (JP).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ELECTRIC STEERING LOCK



(57) Abstract: An electric steering lock (100) capable of outputting a signal correctly indicating an operation state of a steering lock mechanism (8) even when the operation voltage of a lock detector (20, 21) decreases. The electric steering lock includes a CPU (19), a signal hold circuit (22), and an OR circuit (23). When the steering lock mechanism (8) unlocks a steering wheel (16), an unlock sensor provides an H level detection signal (S_{UL}) to the CPU and the signal hold circuit. In response to the detection signal, the CPU issues a state hold command to the signal hold circuit. In response to the state hold command, the signal hold circuit generates an H level hold signal in correspondence with the detection signal. The OR circuit provides an H level signal (S_a) to an immobilizer ECU (7) when at least one of the detection signal from the unlock sensor or the hold signal has an H level.